(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 22 January 2004 (22.01.2004)

PCT

(10) International Publication Number WO 2004/007339 A1

(51) International Patent Classification⁷: 9/065

B66F 17/00,

(21) International Application Number:

PCT/GB2003/002857

(22) International Filing Date:

2 July 2003 (02.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0216204.8

12 July 2002 (12.07.2002) GE

(71) Applicant (for all designated States except US): J.C. BAMFORD EXCAVATORS LIMITED [GB/GB]; Rocester, Staffordshire ST14 5JP (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BROOKS, Richard, Anthony [GB/GB]; 16 Daisy Avenue, Ipstones, Stoke-on-Trent ST10 2LE (GB). JOWETT, Peter [GB/GB]; c/o JCB Research, Rocester, Staffordshire ST14 5JP (GB). (74) Agent: FORRESTER KETLEY & CO.; Chamberlain House, Paradise Place, Birmingham B3 3HP (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROL SYSTEM FOR A LOAD HANDLING APPARATUS



(57) Abstract: A control system (40) for a machine (10) which includes a load handling apparatus (14), the load (L) being moveable relative to a body (12) of the machine by the load handling apparatus (14), the machine (10) including a pivot (C) about which a tipping moment is produced by the load (L), the load handling apparatus (L) including an actuator (24) and being capable of moving the load (L) to a position at which the tipping moment is at a predetermined threshold value, the control system (40) including a sensor (30) to sense the tipping moment and in use, to provide an input to a controller (32), the controller (32) being responsive to the input to influence operation of the actuator (24) so that in the event that the sensor (30) senses that the value of the tipping moment is approaching the threshold value, the speed of movement of the load (L) is progressively reduced.